

KABE 2021 FI Malli	Standard							KingSize						
	Paino ajokunnossa MRO	Kokonaismassa / Kuormaus KG						Paino ajokunnossa MRO	Kokonaismassa / Kuormaus KG					
CLASSIC 470 XL	1335	1450/115	1500/165	1600/265	1700/365			1365	1500/135	1600/265	1700/365			
CLASSIC 520 XL	1418	1530/112	1600/182	1700/282	1800/382	1900/482	2000/582	1448	1560/112	1600/152	1700/252	1800/352	1900/452	2000/552
CLASSIC 560 GLE	1489	1620/131	1700/211	1800/311	1900/411	2000/511		1519	1650/131	1700/181	1800/281	1900/381	2000/481	
CLASSIC 600 GLE								1621	1750/129	1800/179	1900/279	2000/379		
CLASSIC 600 TDL								1611	1720/109	1800/189	1900/289	2000/389		
CLASSIC 600 XL								1652	1750/98	1800/148	1900/248	2000/348		
CLASSIC 600 GDL								1611	1740/129	1800/189	1900/289	2000/389		
CLASSIC 630 GXL								1682	1800/118	1900/218	2000/318			
CLASSIC 660 DGDL								1713	1840/127	1900/187	2000/287			
CLASSIC 780 DGDL								1866	2000/134	2100/234	*3			
BRILIANT 470 XL	1377	1500/123	1600/223	1700/323				1438	1520/82	1600/162	1700/262			
SMARAGD 520 XL	1510	1600/90	1700/190	1800/290	1900/390	2000/490		1540	1630/90	1700/160	1800/260	1900/360	2000/460	
SMARAGD 540 GLE	1519	1620/101	1700/181	1800/281	1900/381	2000/481		1550	1650/100	1700/150	1800/250	1900/350	2000/450	
AMETIST 560 GLE	1540	1700/160	1800/260	1900/360	2000/460			1570	1700/130	1800/230	1900/330	2000/430		
AMETIST 560 XL	1560	1700/140	1800/240	1900/340	2000/440			1590	1700/110	1800/210	1900/310	2000/410		
SAFIR 600 GLE	1652	1800/148	1900/248	2000/348				1683	1820/137	1900/217	2000/317			
SAFIR 600 TDL	1652	1800/148	1900/248	2000/348				1683	1800/117	1900/217	2000/317			
ROYAL 520 XL	1560	1700/140	1800/240	1900/340	2000/440			1590	1700/110	1800/210	1900/310	2000/410		
ROYAL 540 GLE	1581	1700/119	1800/219	1900/319	2000/419			1611	1700/89	1800/189	1900/289	2000/389		
ROYAL 560 XL	1632	1720/88	1800/168	1900/268	2000/368			1662	1800/138	1900/238	2000/338			
ROYAL 560 GLE	1642	1800/158	1900/258	2000/358				1672	1800/128	1900/228	2000/328			
ROYAL 600 XL	1734	1840/106	1900/166	2000/266				1764	1900/136	2000/236				
ROYAL 600 XL FK								1815	1910/95	2000/185				
ROYAL 600 GLE	1744	1900/156	2000/256					1764	1900/136	2000/236				
ROYAL 600 TDL	1724	1900/176	2000/276					1754	1900/146	2000/246				
ROYAL 630 TDL (o 1 akselinen)								1825	1950/125	2000/175				
ROYAL 630 TDL (oo teliakseli)								1856	2000/144	2100/244	2650/794	*4		
ROYAL 630 TDL FK (o 1 akselinen)								1810	1950/140	2000/190				
ROYAL 630 TDL FK (oo teliakseli)								1872	2000/128	2100/228	2650/778	*4		
ROYAL 630 GLE (o 1 akselinen)								1811	2000/189					
ROYAL 630 GLE (oo teliakseli)								1876	2000/128	2100/224	2650/774	*4		
ROYAL 740 GXL								1907	2025/118	2100/193	2650/743	*4		
ROYAL 740 TDL								1917	2050/133	2100/183	2650/712	*4		
ROYAL 740 DGDL (o 1 akselinen)								1872	2000/125					
ROYAL 740 DGDL (oo teliakseli)								2011	2200/248	2650/698	*4			
ROYAL 780 BGXL								2030	2200/170	2650/620	*4			
ROYAL 780 TDL								1994	2200/206	2650/656	*4			
ROYAL 780 TDL FK								2060	2200/140	2650/530				
ROYAL HACIENDA 880 GLE								2220	2800/580					
ROYAL HACIENDA 880 TDL								2195	2800/605					
ROYAL HACIENDA 880 TDL FK								2270	2800/530					
ROYAL HACIENDA 880 DTDL/BTDL								2210	2800/610					
ROYAL HACIENDA 1000 TDL								2336	2800/464					
IMPERIAL 560 XL	1729	1900/171	2000/271					1759	1900/141	2000/241				
IMPERIAL 600 XL								1866	2000/113					
IMPERIAL 600 XL FK								1905	2000/95					
IMPERIAL 630 TDL (o 1 akselinen)								1886	2000/118					
IMPERIAL 630 TDL (oo teliakseli)								1973	2650/677	*4				
IMPERIAL 630 TDL FK (oo teliakseli)								1988	2650/622	*4				
IMPERIAL 740 TDL								2060	2650/590	*4				
IMPERIAL 780 TDL								2120	2650/530	*4				
IMPERIAL 780 TDL FK								2188	2650/462	*4				
IMPERIAL 780 DGLE								2120	2650/530	*4				
IMPERIAL HAC 880 GLE								2310	2800/490					
IMPERIAL HAC 880 TDL								2310	2800/490					
IMPERIAL HAC 880 TDL FK								2380	2800/420					
IMPERIAL HAC 880 DTDL/BTDL								2300	2800/520					
IMPERIAL HAC 1000 TDL								2426	2800/374					

*3 Alustan vaihto mahdollinen: 2650kg

*4 Alustan vaihto mahdollinen: 2800kg

Revision: 2.9.2020

** "Weight in running order" i defined in ECE-R 1230/2012 and is the weight on the vehicle including fuel and liquids fitted with the standard equipment in accordance to the manufactures specification. "Weight in running order" is allowed to vary ±5%